

**A very finely dispersed high-quality paraffin.**

## ADVANTAGES

- Wood protection: PARAFFIGOL PB protects against log shaking, thereby preventing cracks during cutting. It also prevents dehydration and split formation in boards.
- Water repellent for wood materials, particularly for particle boards.
- Wood protection: PARAFFIGOL PB protects against log shaking, thereby preventing cracks during cutting. It also prevents dehydration and split formation in boards.
- Water repellent for wood materials, particularly for particle boards.

## USES

The storage temperature is very important:

- Below 5°C, there is a risk of irreversible separation of the emulsion.
- Above 40°C, there is a risk of water evaporation, and therefore destabilisation of the emulsion.

PARAFFIGOL PB is water-soluble in any proportions.

PARAFFIGOL PB can be applied:

- by brush
- by spray

Characteristics	Standards	Units	Values
Density at 20°C	kg/m <sup>3</sup>	NF T 60-101	940
Water solubility	%	-	100
Cold resistance	°C	-	Down to 5°C
pH	mm <sup>2</sup> /s	NF T 78-103	9.0 ± 1
Viscosity at 20°C	m. Pa.s	DIN 53019	35
Dry matter content	%	-	46 ± 2

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XV-01-1603

Published: 14/03/2016