

100% synthetic* "Fuel Economy" fluid for automatic gearboxes and power steering systems in light and commercial vehicles.

ADVANTAGES and USES

ATF MULTI FE is a universal, high-tech lubricant for extending the life of modern automatic transmissions.

Its 100% synthetic and low viscosity formulation promotes energy saving and offers the following advantages:

- Excellent driving comfort
- Fuel-Economy performance
- Very low pour point
- Excellent low and high temperature properties
- Optimum lubrication from start-up
- Enhanced oxidation resistance for the longest oil change intervals recommended by manufacturers
- Neutral on seals and ferrous and non-ferrous materials
- Helps to reduce CO₂ emissions

The versatility of **ATF MULTI FE** allows it to meet a large number of manufacturer's specifications and therefore numerous uses (list on page 2 and 3).

PHYSICO-CHEMICAL PROPERTIES

| Characteristics | Standards | Units | Values |
|------------------------------|------------|--------------------|--------|
| Colour | - | - | Red |
| Density at 15°C | ASTM D4052 | g/cm ³ | 0.845 |
| Kinematic viscosity at 40°C | ASTM D7042 | mm ² /s | 29.63 |
| Kinematic viscosity at 100°C | ASTM D7042 | mm ² /s | 6.1 |
| Viscosity Index | ASTM D2270 | - | 158 |
| Pour Point | ASTM D97 | °C | - 48 |
| Flash Point | ASTM D92 | °C | 210 |

Technical data sheet



IGOL ATF MULTI FE – Applications

| Manufacturer | Specifications |
|---------------------|--|
| AISIN WARNER | JWS3309/3324/AW-1 |
| BMW - Mini | 83 22 0 142 516, 83 22 0 397 114, 83 22 0 403 248, 83 22 0403 249, 83 22 0 432 807, 83 22 2 152 426, 83 22 2 413 / 477 (ATF7), 83 22 9 400 275 83 22 9 407 738, 83 22 9 407 858, 83 22 9 407 859, ATF 3+, L12108 |
| CHRYSLER/DODGE/JEEP | P/N 05127382AA / P/N 68043742AA P/N 68157995AA / ATF+/+2/+3/+4 |
| FIAT | 9.55550-AV5 for ZF Automatic 8 and 9 speed 9.55550-AV-2 for 6 speed Automatic transmissions |
| FORD | Mercon ULV** LV/V/SP / WSS-M2C922-A1 |
| GM | DEXRON ULV ATF** DEXRON VI/II/IID/IIIE/IIIG/IIIH/Suffix A |
| HONDA | Honda DW-1/3.0/3.1 ATF-Z1 (exclud CVT) |
| HYUNDAI / KIA | SP-II/-III/-IV/-IV RR/RED-1K/NWS 9638 |
| ISUZU | Isuzu ATF II/III Isuzu WSI |
| JAGUAR/ LAND ROVER | Jaguar fluid 8432/20238/20292/21044 Land Rover P/N LR0022460- Land Rover P/N TYK500050 |
| JASO | M315 Type 1A LV |
| MASERATI | MASERATI 231603 M-1375.4 |
| MAZDA | Mazda ATF FZ** M-III/Type T-IV |
| MERCEDES | MB 236.5/236.6/236.7/236.8/236.9/236.10/236.11MB/236.12 236.14/236.15**(7G-TRONIC)/236.16**/236.17** (9G-TRONIC)/236.41 |

Technical data sheet



IGOL ATF MULTI FE – Applications

| Constructeurs | Spécifications |
|------------------|--|
| MITSUBISHI | Mitsubishi SP-II/III/J2/J3/PA |
| NISSAN | Nissan Matic D/J/K/S/W |
| PSA | PEUGEOT AW-1, RP 9734 R7 for EAT6 transmissions |
| PORSCHE | Porsche P/N 000 043 304 00 |
| SUZUKI | Suzuki ATF 3314/3317 |
| SUBARU | Subaru ATF HP |
| TOYOTA/LEXUS | 00289-ATFWS, 08886-02303, 08886-02305, 08886-80803 ATF Type T-IV, ATF WS, JWS 3324, NWS 9638 |
| VOLKSWAGEN Group | VW G 052 025 / G 052 055 / G 052 162 / 052 533 / G 052 990 VW G 055 005 / G 055 025 / G 055 540 / G 060 162 |
| ZF | ZF TE-ML 11A/11B ZF Lifeguard 9, Lifeguard 8 et Lifeguard 6 |

**Contains HC group III hydrocracked base oils*

***Corresponds to the application excluding Fuel Economy benefits*

Note: Before use, always check the manufacturer's recommendations in the maintenance manual.

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : IV-IGOL044-2112
Date of issue : 19/06/2024

Technical data sheet

