

Synthetics lubricants developed for the food-processing industry.

PERFORMANCES

Specifications:

- NSF H1 category-Registration no. : 145727 (grade 150)
- NSF H1 category-Registration no. : 145748 (grade 320)

ADVANTAGES

Synthetics lubricants specially developed for chains & conveyors lubrication.
CHAINE HT AL has a thermal stability which allows to reduce significantly deposits formation.
Compatible with all mineral lubricant.

USES

- Greasing with oilcan, drip irrigation, by pump or automatic fogging system on conveyor lines subject to high temperatures.
- Badcock – Krantz chains...
- Overhead conveyor.

Characteristics	Units	Standards	150	320
Density at 15°C	Kg/m ³	NF T 60-101	945	960
V.O Flash Point	°C	NF T 60-118	270	275
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	153.2	325.6

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref. : VIII-119-1510
Date of publication : 19/10/2015