

A synthetic lubricant (PAO) for vacuum pumps and pneumatic circuits in agri-business.

PERFORMANCES

COMPRAL VI 100 can be used wherever accidental contact between oil and foods is a possibility. Compliant with the HACCP requirements.
Category H1, Registration no.: pending

ADVANTAGES

- 100% synthetic formulation
- Longer oil change intervals

USES

- Vacuum pumps
- Pneumatic equipment
- Hydraulic circuits operating at low temperature

Characteristics	Units	Methods	Values
Density at 15°C	kg/m ³	NF T 60-101	840
COC flash point	°C	NF T 60-118	272
Pour point	°C	NF T 60-105	<-40
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	98.5
Viscosity index	-	NF T 60-136	156

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XIII-IGOL004-1512
Published: 01/03/2016