

An extra-high purity mineral oil-based lubricant.

PERFORMANCES

Specifications:
NF ISO 6743/ 3A

ADVANTAGES

COMPRESSOR R has been formulated quite simply for rotary air compressors, thanks to additives designed to provide good anti-oxidant, anti-corrosion, anti-wear and extreme pressure properties.

USES

COMPRESSOR R is aimed at lubricating rotary vane and rotary screw air compressors under normal operating conditions.

Characteristics	Standards	Units	32	46	68	100
Density at 15°C	NF T 60-101	kg/m ³	872	877	882	885
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	33	42	71.4	101.5
Kinematic viscosity at 100°C	NF T 60-100	mm ² /s	5.5	6.3	8.9	11.4
Viscosity Index	NF T 60-136	-	102	96	97	98
Pour point	NF T 60-105	°C	- 9	-10	-10	-8
COC Flash point	NF T 60-118	°C	210	232	240	245

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: VIII-20-1503

Published: 19/12/2016