

A lubricant* for petrol and diesel engines in top-of-the-range passenger vehicles.

USES

E.LUB 5W-40 satisfies the latest specifications of ACEA manufacturers, and makes it possible to lubricate most passenger vehicles on the road in Europe with a single product.

PERFORMANCES

Standards: ACEA A3/B3/B4
API SN/CF

ORGANISATIONS & MANUFACTURERS - Scope of application -

ACEA A3/B4: For "high performance" petrol and direct injection diesel engines.

ACEA A3/B3: For "high performance" petrol and indirect injection diesel engines.

API SN: Petrol = SM + exhaust system protection + turbocharger.

API CF: Diesel, since 1994 (not recommended in the USA for light-duty vehicles).

Characteristics	Standards	Units	Values
Viscosity at 40°C	ASTM D7042	mm ² /s	86.0
Density at 15°C	ASTM D4052	g/cm ³	0.856
Viscosity index	ASTM D2270	-	176
Pour point	ASTM D97	°C	-39
CCS @ -20°C	ASTM D5293	mPa.s	6200

*Contains group III base oils

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: I-101-1503
Published: 27/07/2020

