

**A lubricating grease aerosol based on complex calcium soap, plus codex white oils.  
Reserved for professional use**

## PERFORMANCES

Meets the criteria of NSF category H1 (grease and solvent contained in the aerosol) no. 146021.  
Range of use: from -5°C to +140°C.

## ADVANTAGES

- Adhesiveness: High adhesiveness on metal parts, preventing spatter even at high speeds.
- Leaching: Completely insoluble in water and steam.

## USES

Agri-business (harvesting machines, dairy, meat, flour and fruit industries.)  
Plain bearings subject to repeated vibrations and impacts. Joints and chains working in very wet atmospheres (canneries, fish industry, animal feed processing)  
Slides and cams. Open or covered gears near bottling, packing or bagging lines, etc.

**The aerosol cans must be used within one year of delivery for optimum use; returns will not be accepted after this time.**

Characteristics	Standards	Units	Values
Colour	-	-	Beige
Texture	-	-	Smooth/adhesive
Penetration	NF T 60-132	1/10 mm	310/340
DP	NF T 60-102	°C	> 180
4-ball weld	ASTM D2596	kg	> 160

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XVII-56-A-1508  
Published: 24/07/2023