

## A monograde oil.

An anti-oxidant, anti-wear lubricant for 4-stroke petrol engines.

### PERFORMANCES

**Standards:** API SE/CC

### ORGANISATIONS & MANUFACTURERS - Scope of application -

**API SE:** For petrol engines in passenger vehicles and lorries made since 1971. SE oils can replace SC oils. Compared to the previous category, SC oil offers better resistance against and 'cold sludge' formation at low temperatures. Furthermore, the engine is better protected against rust formation.

**API CC:** Standard from 1961, for older engines dating from this time. Characteristic service for certain naturally aspirated, supercharged or turbocharged diesel engines in moderate to tough service, and certain high-powered petrol engines. Oils aimed at this service provide protection against deposit formation at high temperatures and corrosion of bearing blocks in diesel engines and also against rust, corrosion and deposit formation at low temperatures in petrol engines.

Characteristics	Standards	Units	50	40	30
Density at 15°C	NF T 60-101	kg/m <sup>3</sup>	856	888	881
Kinematic viscosity at 100°C	NF T 60-100	mm <sup>2</sup> /s	18.3	14.5	11.05

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: I-IGOL001-1507  
Published: 18/01/2018

