

**A flushing fluid for hydraulic systems.**

<b>DESCRIPTION &amp; APPLICATIONS</b>
---------------------------------------

HYDRO CLEAN is a concentrated fluid for dissolving gums and deposits forming in hydraulic circuits, especially in slide valves.

HYDRO CLEAN has no effect on the seals or metals present in these circuits.

HYDRO CLEAN, incorporated into the service oil, prevents production stoppages.

<b>USES</b>
-------------

Cleaning and flushing hydraulic circuits in machine tools equipped with HL, HM or HV hydraulic fluids.

Cleaning and flushing heat transfer circuits operating with mineral oil: water baths, preheaters, moulds, etc.

For use in mixture with these oils approximately 24 hours before each draining operation.

Concentration: 5 to 15 % HYDRO CLEAN depending on the circuit condition.

Do not use HYDRO CLEAN in hydraulic circuits equipped with non-inflammable fluids such as glycol/water, or in reverse emulsion, or in circuits equipped with synthetic fluids.

Characteristics	Units	Methods	Values
Appearance / Colour	-	-	Brown fluid
Density at 15°C	NFT 60-101	kg/m <sup>3</sup>	890
Kinematic viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	18
COC flash point	NFT 60-118	°C	128

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: VIII-110-1603

Published: 14/03/2016

Technical data sheet