

A special lubricant for rear axles and screw reduction gears.

USES

Rear worm axles with a bronze crown wheel.

Industrial screw reduction gears incorporating a bronze crown wheel.

IGOL R is miscible with castor-based oils, and with extreme pressure oils.

IGOL R is non-miscible with mineral oils.

PRECAUTIONS FOR USE

If the equipment to be lubricated contains a castor oil-based lubricant, IGOL R can be used for topping up without any particular precautions.

If the equipment was lubricated with a mineral oil, it is advisable to drain the oil and rinse out carefully with diesel fuel before refilling with IGOL R.

Characteristics	Units	Methods	Values
Kinematic viscosity at 40°C	mm ² /s	ISO 3104	235
Kinematic viscosity at 100°C	mm ² /s	ISO 3104	18
Density at 15°C	kg/m ³	ISO 12185	956
Viscosity index	-	ISO 2909	81
Pour point	°C	ISO 3016	-21

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: VI-01-1511
Published: 11/04/2016