

**A solvent/degreaser**  
**Reserved for professional use.**

<b>DESCRIPTION &amp; APPLICATIONS</b>
---------------------------------------

Cleaning mechanical parts Ready-to-use  
 Use in tank, or apply by cloth or brush  
 A complex mixture of hydrocarbons with high solvent power and high evaporation speed.  
 It is free from chlorinated, fluorinated or brominated compounds.

IGOSOLVE SC 6 was specially designed for:

- cold degreasing,
- inter-operation degreasing in machining, manual or by immersion;  
degreasing parts before protection,
- degreasing high-precision parts,
- eliminating synthetic resin-based anti-rust films, maintaining and cleaning tools.

IGOSOLVE SC 6 can be used with ultrasound, provided that the bath temperature is set to 15°C below the flash point of the fluid in question.

IGOSOLVE SC 6 can be used both cold and hot. In the latter case, the bath temperature should be set to 15°C below the flash point, in order to optimise the fluid solvent power and the safety aspect.

<b>ADVANTAGES</b>
-------------------

- Rapid drying
- High solvent power
- No corrosive action on the usual metals.

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Colourless fluid
Density at 15°C	NFT 60-101	kg/m <sup>3</sup>	750-850
COC flash point	NFT 60-118	°C	>61

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: X-124-1603  
 Published: 23/08/2021