

**A special liquid for inflating tyres.**

LESTOGEL is a special antifreeze for inflating and ballasting tyres, comprising inhibited glycols and possessing good anti-corrosion properties.

LESTOGEL does not attack rubber, pump components or valves.

**PERFORMANCES**

Meets AFNOR standard NF R 15-601.

**ADVANTAGES**

- Borax-free
- Nitrite-free
- Amine-free

**USES**

LESTOGEL is used diluted in demineralised water, to prevent formation of potentially damaging ice blocks in the inner tubes.

<b>Protection, °C</b>	-10	-18	-24
<b>Lestogel (% by volume)</b>	5	10	15

LESTOGEL can be used among other things for agricultural or forestry tractors, and for snow ploughs.

LESTOGEL contains monoethylene glycol. For public health protection, especially children, LESTOGEL contains a product giving it a bitter taste.

Characteristics	Methods	Units	Values
Freezing point at 33% vol.	NF T 78-102	°C	-18
Alkaline reserve	NF T 78-101	ml	15
Density	NF T 60-172	kg/dm <sup>3</sup>	1.12
Refraction coefficient	NF R 15-602-2	-	1.435
Ash content	NF R 15-602-3	%	1.25
Boiling point	NF R 15-602-4	°C	163
Flash point	NF M 07-019	°C	125
Foaming tendency at 33% vol.	NF R 15-602-5	-	-
Foam volume	-	ml	100
Foam disappearance	-	s	10

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: X-25-1503  
Published: 18/03/2016