

Highly fluid oils for greasing very fast-moving mechanisms, produced from refined base oils and additives providing oxidation and corrosion resistance properties.

PERFORMANCES

Type FC (standard ISO NF E 60-200)

USES

Circulation, oil bath or mist greasing of bushings and roller bearings operating at very high speeds in clutch-equipped components

ADVANTAGES

These oils are free from anti-wear additives, which enables them to be used in clutch-equipped components.

Characteristics	Unit	Standards	Values		
Grades	-	-	2	5	10
Density at 15°C	kg/m ³	NF T 60-101	802	812	835
COC flash point	°C	NF T 60-118	90	104	154
Fire point	°C	NF T 60-118	100	120	170
Pour point	°C	NF T 105	-40	-40	-30
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	2.1	4.7	10.0

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: VIII- 85-1603
Published: 14/03/2015