

A neat oil for metalworking or woodworking.

DESCRIPTION & APPLICATIONS

Metalworking (light duty operations). Sawing and cutting wood.
Processing logs and staves in sawmills. A colourless, transparent and odourless fluid.
A non-toxic preparation, **OIL CUT A 15L** is free from chlorinated, fluorinated and aromatic compounds.
OIL CUT A 15 L is tailored to ferrous and non-ferrous metalworking (light-duty operations).
OIL CUT A 15 L lubricates saw blades, work tops and wood processing components.

ADVANTAGES

Low volatility: no volatile organic carbon (VOC) emissions, no odours in the workplace, reduces consumption volumes, as well as lubrication and storage costs.
Optimum health and safety conditions (non-toxic preparation, high flash point, low risks of skin irritation).
Lubricant authorised for incidental contact with food (level NSF H1).
Cooling power (product fluidity) and friction reducing power, which improves the service life of lubricated tools and components.
Good anti-corrosion power.
Non-toxic fluid.
Colourless fluid.
Fluid containing less than 200 ppm sulfur.

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Colourless fluid
Pour point	NF T 60-105	°C	-9
Density at 15°C	NFT 60-101	kg/m ³	840
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	15
COC flash point	NFT 60-118	°C	180

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XI-115-1603
Published: 15/03/2016