

**A neat oil for metalworking.**

<b>DESCRIPTION &amp; APPLICATIONS</b>
---------------------------------------

Lapping, grinding, finishing Bar turning

The specific additives in OIL CUT B 16 F provide a high level of extreme pressure and anti-wear. This property reduces tool wear and heat generation, which, coupled with well-targeted anti-oxidant protection, helps maintain the fluid's superior performance level for longer.

<b>ADVANTAGES</b>
-------------------

- No chlorine
- Anti-wear Lubricity
- Cooling power
- Wettability
- Versatile

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Brown fluid
Density at 15°C	NFT 60-101	kg/m <sup>3</sup>	878
Kinematic viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	17
COC flash point	NFT 60-118	°C	170

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XI-116-1603  
Published: 15/03/2016

Technical data sheet