

A neat oil for metalworking.

DESCRIPTION & APPLICATIONS

Sawing, cutting, drilling, tapping.
Micro-spraying.

A synthetic lubricant with high thermal stability, aimed at working ferrous metals and aluminium.

Its fluidity, combined with specific additives, make it suitable for use in a spraying system.

This micro-mist dispensed over the cutting area meets the requirements of the toughest jobs.

ADVANTAGES

- No chlorine
- No sulfur
- Lubricity, polarity.
- Anti-misting properties.
- Thermal stability.
- Prevents built-up edge formation, no gumming

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Yellow fluid
Density at 15°C	NFT 60-101	kg/m ³	920
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	47
COC flash point	NFT 60-118	°C	310

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XI-93-1603
Published: 15/03/2016

Technical data sheet