

A neat oil for metalworking.

DESCRIPTION & APPLICATIONS

Straightening steel wires
 Machining stainless steels, hard steels, alloy steels.

An extreme pressure cutting oil for machining hard steels and particularly stainless steels.

Prevents seizing and metal tearing.

Enhanced lubricity, facilitating swarf sliding over the tool, by reducing the friction coefficient at the tool/swarf interface.

Strong anti-wear and extreme pressure properties.

ADVANTAGES

- Anti-wear
- Enhanced lubricity
- Extreme pressure
- No chlorine

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Brown fluid
Density at 15°C	NFT 60-101	kg/m ³	921
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	1724
COC flash point	NFT 60-118	°C	252
Fire point	NFT 60-118	°C	268

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XI-122-1603

Published: 15/03/2016