

A neat oil for metalworking.

DESCRIPTION & APPLICATIONS

Cold heading on steels, brass and stainless steel.

A sulfo-chlorinated extreme pressure cutting oil tailored to difficult machining.

Lubricity enhanced by the presence of additives which give the lubricating film increased resistance, to limit wear phenomena.

ADVANTAGES

- Extreme pressure
- Enhanced lubricity
- Neutrality to elastomers and paints
- Presence of an additive protecting the surfaces of copper-based metals

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Brown fluid
Density at 15°C	NFT 60-101	kg/m ³	958
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	8.8
COC flash point	NFT 60-118	°C	146
Fire point	NFT 60-118	°C	154

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XI-97-1603
Published: 15/03/2016

Technical data sheet