

A neat oil for metalworking.

DESCRIPTION & APPLICATIONS
----------------------------

- Drilling
- Tapping

A drilling/tapping fluid particularly suited to hard materials (alloy steels and stainless steels).

Specifically suited to very difficult jobs on refractory steels.

Its viscosity was designed to enable large-diameter and high-depth tapping. This specific viscosity, combined with the extreme pressure, adhesion and lubricity properties of the fluid, ensures better surface finishes and longer tool service life.

ADVANTAGES
------------

- No chlorine
- Extreme pressure
- Adhesiveness
- Lubricity
- Tool service life

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Green fluid
Density at 15°C	NFT 60-101	kg/m <sup>3</sup>	910
Kinematic viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	365

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XI-101-1603  
Published: 15/03/2016

Technical data sheet