

**A neat oil for metalworking.**

**DESCRIPTION & APPLICATIONS**

Cutting  
Pressing  
Applied by spraying, coating rollers, drip feed or brush

An extreme pressure lubricant created especially for performing the toughest cutting and pressing operations, thanks to its outstanding lubricity and perfect wettability qualities both hot and cold.

Specific additives employing a synergy of chlorine-free EP agents enhance its performances, and enable the most complex operations to be performed on all thicknesses and on hard-to-work materials (HLE, stainless steel, etc.)

Extends tool service life.

After processing, the residual oil film provides temporary protection of the plates during storage prior to packaging or between operations.

Its design allows for degreasing in the organic solvent phase or through chemical degreasing by alkaline detergents.

**ADVANTAGES**

- No chlorine
- Extreme pressure
- Lubricity
- Wettability

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Light brown fluid
Density at 15°C	NFT 60-101	kg/m <sup>3</sup>	1026
Kinematic viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	150.1

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XI-90-1503  
Published: 31/03/2015

Technical data sheet