

An evanescent oil for metalworking.

DESCRIPTION & APPLICATIONS

Pressing, bending, forming operations.
 Machining

Applied by spraying, coating rollers, drip feed or brush.
 A chlorine-free evanescent fluid which is used for deformation metalworking or machining.
 Its anti-wear and extreme pressure additives obtain excellent surface finishes, and extend tool service life.

Leaves an imperceptible waxy protective film. The parts can thus undergo a subsequent surface treatment or be stored, with the residual film providing protection against corrosion.

ADVANTAGES

- No chlorine.
- Extreme pressure.
- Versatile.
- Imperceptible waxy protective film.

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Yellow fluid
Density at 15°C	NFT 60-101	kg/m ³	780
COC flash point	NFT 60-118	°C	>62

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XI-167-1503
 Published: 31/03/2015