

An evanescent oil for metalworking.

## DESCRIPTION & APPLICATIONS

Difficult cutting & pressing operations.

Applied by spraying, coating rollers, drip feed or brush.

A chlorinated extreme pressure lubricant with enhanced degreasability, which was especially created to perform tough cutting & pressing operations.

This fluid's anti-wear performance level extends tool service life.

After processing, the residual oil film provides temporary protection of the plates during storage prior to packaging or between operations.

Manufactured parts do not pose any problems in welding operations, even if prior degreasing has not been performed.

## ADVANTAGES

- Extreme pressure
- Enhanced degreasability
- Oily protective film

| Characteristics     | Standards  | Units             | Values       |
|---------------------|------------|-------------------|--------------|
| Appearance / Colour | -          | -                 | Yellow fluid |
| Density at 15°C     | NFT 60-101 | kg/m <sup>3</sup> | 910          |

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: XI-112-1603  
Published: 16/03/2016