

A lubricating grease made from a lithium and calcium soap base, plus refined mineral oils.

PERFORMANCES

DIN 51502:KP2K-30
ISO 6743 / 12924:L-XCCEB2

Drop point: > 185°C
Range of use: -30 to + 140°C
EP welding: > 280 kg

ADVANTAGES

Centrifuging

The grease structure and the adhesiveness polymers it contains enable it to withstand the effects of centrifuging.

Pumpability

Easily pumpable in distribution systems (even cold).

USES

Automobiles / HGVs / Agriculture / Construction

Perfect Plus is a multi-purpose grease for conditions of use entailing heavy loads and repeated shocks.

Industry

For general greasing of machines tools.
For ball and roller bearings.

Characteristics	Standards	Units	Values
Colour	-	-	Green
Texture	-	-	Smooth
NLGI grade	-	-	2
Penetration	NF T 60-132	1/10 mm	265/295
EMCOR	NF T 60-135	-	0/1
Water Wash Out	ASTM D1264	%	>3
Density	-	kg/m ³	886

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref. IX-05-1509
Date of publication : 06/10/2016