

Special lubricant for pneumatics tools

PERFORMANCES

Specifications :

Type P (standards ISO 6743/0 et NF T 60-162).

ADVANTAGES

Lubricants for pneumatics tools greasing, developed with refined minerals oils and specifics additives providing antioxydant, anticorrosive and extreme pressure properties.

They ensure an excellent lubrication for equipments submitted to impacts and percussions and a good protection against moisture, always present in compressed air.

USES

Greasing by pneumatics tools oil mist:

- Pneumatic drills
- Presses
- Vibrators

Characteristics	Standards	Units	Values				
			22	32	46	68	100
Grades	ISO-VG	-					
Density at 15 °C	NF T 60-101	mg/m3	864.3	875.3	879.3	884.4	889
Kinematic viscosity at 40 °C	NF T 60-100	mm2/s	22.1	33.1	48	69.5	101
Kinematic viscosity at 100 °C	NF T 60-100	mm2/s	4.49	5.71	7.21	9.2	11.3
V.O Flash point	NF T 60-118	°C	185	198	207	210	252
Pour point	NF T 60-105	°C	-33	-30	-28	-24	-18

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref. : VIII- 03-L-1510
Date of publication : 01/03/2016