

A 100 % synthetic oil.

PERFORMANCES

Standards :

ACEA E4/E7

Specifications :

SCANIA LDF-3*
VOLVO VDS-3
MERCEDES MB 228.5
MAN M 3277
RVI RLD-2/RXD
DEUTZ DQC III-10
MTU Type 3
Cummins CES 20072
MACK EO-N

***Approved quality.** Use recommended under manufacturers' warranties.

ADVANTAGES

A very high-performance lubricant, formulated to meet the needs of new Euro VI diesel engines, requiring a long-drain engine oil meeting Scania standard LDF-3.

Suitable for lubricating naturally aspirated and supercharged diesel engines: HGVs, buses, construction and agricultural machinery.

Also suitable for Euro V and earlier powertrains.

Enables longer oil change intervals, to meet **Scania specification LDF-3.**

Fiche technique



PHYSICO-CHEMICAL PROPERTIES

Characteristics	Standards	Units	Values
Density at 20°C	ASTM D4052	g/cm ³	0.862
Viscosity at 40°C	ASTM D7042	mm ² /s	92.5
Viscosity at 100°C	ASTM D7042	mm ² /s	14.3
HTHS viscosity	ASTM D4683	cP	3.95
Viscosity index	ASTM D2270	-	161
Pour point	ASTM D97 B	°C	-42
Flash point	ASTM D92	°C	228
TBN	ASTM D2896	Mg KOH/g	15.8

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: III-115-1601
Published: 16/05/2022

Fiche technique

