

High-performance synthetic lubricant* that provides protection, cleanliness, and extended engine life.

PERFORMANCES

Standards :

ACEA A3/B4
API SN

Spécifications :

MB 229.1
Renault RN0700/0710

ADVANTAGES

PROCESS S 5W-40 ensures excellent cold-weather flow, maintains stable viscosity at high temperatures, and offers great versatility for gasoline and diesel engines without particulate filters (DPF).

PHYSICO-CHEMICAL PROPERTIES

Characteristics	Standards	Unit	Values
Specific gravity at 15°C	ASTM D4052	g/cm ³	0.850
Cinematic viscosity at 40°C	ASTM D7042	mm ² /s	85.7
Cinematic viscosity at 100°C	ASTM D7042	mm ² /s	14.1
Viscosity Index	ASTM D2270	-	170
Pour point	ASTM D97 B	°C	-44
Flash point	ASTM D92	°C	232

**Contains Group III base oils*

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document Ref.: I-IGOL045-2603
Date of publication: 03/04/2026

Technical data sheet

