

Semi-synthetic lubricants for 2-stroke engines in chainsaws, tillers and mowers.

PERFORMANCES

Standards:

API: TC+ in 2% dilution

ADVANTAGES

PROFIL HI-TECH 2T contains viscous esters, replacing the thick petroleum bases in general use.

These viscous esters provide better lubricating properties, which prevents risks of tightening, with no formation of carbon deposits by burning, which ensures high cleanliness of the piston grooves, segments and exhaust ports.

USES

PROFIL HI-TECH 2T is a semi-synthetic oil for use in 2-stroke engines fitted in chainsaws, tillers, lawnmowers, etc.

It contains solvent to enable it to be used in separate greasing, and to facilitate mixing in petrol.

It is reserved for professional use.

In mixture, the dose is 2 %, according to manufacturer's recommendations.

Fuel	Dose 2% (50:1)
1 Litre	20 ml
2 Litres	40ml
5 Litres	100 ml
10 Litres	200 ml

Fiche technique



PHYSICO-CHEMICAL CHARACTERISTIC

Caractéristiques	Méthodes	Unités	Valeurs
Colour	Visuel	-	Rouge
Density at 15°C	NF T 60-101	Kg/m3	890
Kinematic viscosity at 40°C	NF T 60-100	Mm ² /s	64
Kinematic viscosity at 100°C	NF T 60-100	Mm ² /s	10.5
Viscosity index	NF T 60-136	-	>110
COC flash point	NF T 60-118	°C	148
Pour point	NF T 60-105	°C	-18

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: II-51-C-1507
Published: 22/07/2024

Fiche technique

