

Semi Synthetic oil.

## PERFORMANCES

### Standards :

ACEA A3/B4  
API SN

### Spécifications :

Renault RN 700  
PSA B71 2300  
Mercedes MB 229.1  
VW 501.01 / 505.00

## ADVANTAGES

**IGOL PROFIVE B4R 10W-40** is a lubricant designed to meet the needs of all types of engines: gasoline or diesel, with or without turbo, direct or indirect injection.

- SAE 10W-40 grade formulation for all-season use
- High shear resistance
- Anti-oxidation: viscosity stability over time
- Detergent and dispersant properties

Compatible with catalytic converters, but not with FAP/DPF particulate filters

## PHYSICO-CHEMICAL CHARACTERISTICS

Characteristics	Standards	Units	Values
Viscosity 40°C	ASTM D7042	mm <sup>2</sup> /s	88.6
Viscosity 100°C	ASTM D7042	mm <sup>2</sup> /s	13.7
Viscosity index	ASTM D2270	-	158
Pour point	ASTM D97	°C	-42
Flash point	ASTM D92	°C	225
Density at 20°C	ASTM 4052	g/Cm3	0.866

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : I-IGOL030-2206  
Date of issue : 21/06/2021

