

100% synthetic oil.

PERFORMANCES

Standard :

ACEA C2

API SP

Spécifications :

Peugeot/Citroën Automobiles PSA B71 2312*

Peugeot/Citroën Automobiles PSA B71 2302

Fiat 9.55535-GS1

Fiat 9.55535-DS1

* **Approved quality.** Use recommended under manufacturers' warranties.

ADVANTAGES

PROFIVE CRYSTAL 0W-30 is a next-generation engine lubricant, specifically formulated to meet the strict requirements of the PSA B71 2312 specification from the Peugeot/Citroën Group (STELLANTIS).

Its **MID SAPS** formulation (low content of sulphated ash, phosphorus, and sulfur) is optimized to ensure full compatibility with exhaust after-treatment systems (DPF, SCR, etc.), extending their service life while maintaining optimal efficiency in reducing pollutant emissions.

Compliant with **ACEA C2** category, this lubricant features a controlled **HTHS (High Temperature High Shear)** viscosity, providing an ideal balance between engine protection and fuel economy. It enables significant savings, particularly in modern engine designs.

Thanks to its **SAE 0W-30 viscosity grade** and **100% synthetic base**, PROFIVE CRYSTAL 0W-30 delivers excellent cold-start performance, ensuring instant lubrication of critical engine components while maintaining enhanced protection against wear, deposits, and sludge.

Technical data sheet



PHYSICO-CHEMICAL CHARACTERISTICS

Characteristics	Standards	Units	Values
Density at 20°C	ASTM D4052	g/cm ³	0.844
Viscosity 40°C	ASTM D7042	mm ² /s	51.3
Viscosity 100°C	ASTM D7042	mm ² /s	9.8
Viscosity index	ASTM D2270	-	181
Pour point	ASTM D97	°C	-49
Flash point	ASTM D92	°C	>219
TBN (alkaline reserve)	ASTM D2896	Mg KOH/g	10.1

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : I-IGOL042-2506
Date of issue : 18/06/2025

Technical data sheet

