

An extreme pressure black grease, specially designed for semi-trailer supports, comprising a mixed lithium-calcium soap and refined mineral oils base.

PERFORMANCES

DIN 51502:KPF2K-15
 ISO 6743 / 12924:L-XBCHB2
 Drop point > 170°C

ADVANTAGES

- Excellent adhesion on pressed cast iron or steel supports.
- Prevents locking.
- Facilitates removal.
- Completely insoluble in water.
- Ensures complete water resistance.

USES

HGVs

- Greasing supports, control mechanisms, slides and racks.
- Threads subject to high forces and pressures.
- Drill bit screws (construction)
- Greasing for drill pipe threads.

Characteristics	Standards	Units	Values
Colour	-	-	Black
Texture	-	-	Smooth
NLGI grade	-	-	2
Penetration	NF T 60-132	1/10 mm	265/295
Drop point	METTLER	°C	> 170
4-ball weld	ASTM D 2266	kg	> 500
4-ball wear Shell	ASTM D 2596	mm	<0.5

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: IX-15-1509
 Published: 17/09/2015