

100% synthetic oil.

Developed on the back of a very high performance Full SAPS technology, designed specially for recent powerful petrol, diesel, turbo-diesel, direct or multi-valve injection vehicles.

PERFORMANCES

Standards : ACEA A3/B3/B4-12
API SN/SM/CF

Specifications :

Renault RN 700/0710*

Peugeot/Citroën Automobiles B71 2296

Mercedes MB p.226.5 / p.229.5

BMW LL-01/ LL-98

OPEL GM –LL-B-025

VW 502.00/505.00

Porsche A40

FIAT 9.55535-M2

CHRYSLER MS 12991

* **Approved quality.** Use recommended under manufacturers' warranties.

ORGANISATIONS & MANUFACTURERS - Scope of application -

ACEA A3/B3/B4-12: For "High Performance" Petrol and Direct Injection diesel engines.

API SN: Petrol = SM + exhaust system protection + turbocharger.

API SM: Petrol, starting from 2005, with reduced energy consumption.

API CF: Diesel, starting from 1994 (not recommended in the E.U in light vehicles).

PSA B71 2296: For any engine from the PSA Diesel group without FAP and Petrol, unless 1.6L THP, 1.6L VTI, 1.4L VTI (PSA B71 2290) petrol engine and all engines built before 2000. Maximum oil change interval.

RENAULT RN 700: For any engine from the RENAULT group, Renault turbo-charged petrol [translator's note: something is missing here] Kms or 1 year.

RENAULT RN 710: For any engine from the RENAULT Atmospheric petrol group (except Renault Sport) , diesel engine without FAP unless 1.5L dCi diesel engine without FAP (< 100 HP), oil change interval 20,000 km or 1 year. Applies also to the 2.2 dCi engine with FAP.

Technical data sheet



MB 226.5: Specification equivalent to Renault RN0710, intended for "Smart" vehicles and the new "Citan" models fitted with the M281, M200 and M282 engines (Renault engines to which a MB code has been assigned).

GM LL-B-025: For any engine from the GM Diesel group (with or without FAP) built before 2010.

BMW LL-01: For any petrol or diesel engine produced between 2001 and 2004.
Covers BMW LL-98.

PORSCHE A40: For any PORSCHE engine except Cayenne V6 and diesel version.

VW 502.00: ACEA A3-96 level plus PV1449 engine test for petrol engine.

VW 505.00: ACEA B3 level for diesel engine, with natural aspiration or supercharged.
Maximum oil change interval 15,000 km.

FIAT 9.55535-M2: Fiat engine oil specification for gasoline engines. OEM recommended product also meets ACEA B3-04/B4-04, GM-LL-B-025.

Technical data sheet

Characteristics	Standards	Units	Values
Density at 15°C	NFT 60-101	Kg/m ³	856
Viscosity at 40°C	ASTM D445	mm ² /s	86
Viscosity at 100°C	ASTM D445	mm ² /s	14.5
Index viscosity	NF T 60-136	-	176
Pour point	ASTM D2602	°C	-43
CCS @ -30°C	ASTM D5293	mPa.s	6200

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : I-20-18510
Published: 29/10/2018

