

**A synthetic grease for high-speed and low-temperature applications.**

## PERFORMANCES

NSF Category H1. Registration no: -  
Range of use: from - 50°C to +120°C (max. 140°C)

**All components meet the requirements of the FDA (Food and Drug Administration) under title 21 of the CFR (Code of Federal Regulations).**

## ADVANTAGES

- Excellent durability at very low temperatures and high speeds
- Lubricating power maintained
- Good water and corrosion resistance

## USES

- Roller bearings & slides for deep freezers
- Hook slides for coolers
- Joints, various mechanisms, cables, racks
- Conveyor chains
- Plain bearing blocks
- Lubricating any equipment exposed to very low temperatures or high speeds, mainly used in agri-business

Characteristics	Standards	Units	Values
Appearance / Colour	-	-	Smooth / White
Nature of soap	-	-	Aluminium complex
Nature of base oil	-	-	Synthetic
Base oil viscosity at 40°C	ASTM D7152	mm <sup>2</sup> /s	42
Grade	NLGI	-	2
Drop point	NFT 60-102	°C	>240
Range of use	-	°C	-50 to +120

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: X-IGOL007-1603  
Published: 26/09/2018