

**A multi-purpose oil (UTTO), used for hydraulic and mechanical transmissions in agricultural and construction machinery subject to heavy loads.
A synthetic fluid specially designed for continuous variation transmissions (CVT) in tractors**

PERFORMANCES

Standards:
API GL-4

Specifications:
CNH MAT 3540/3525
Ford M2C86-C, M2C134-D
John Deere J20C/D
Massey Ferguson M1143/M1145
Allison C4, Cat TO-2, Case MS 1210
FNHA-2-C-200.00/201.00
Volvo WB 101
Valtra G2-08
ZF TE-ML 03E/05F/06K/17E/21F
Claas CVT

ADVANTAGES

The TICMA FLUID XT XTREM additive system ensures very good lubrication of gear trains and hydraulic controls.

TICMA FLUID XT XTREM contains extreme pressure additives which retain the protective film and reduce shearing effects on the gears, even under load.

TICMA FLUID XT XTREM's anti-wear and anti-corrosion properties ensure the gear protection.

TICMA FLUID XT XTREM has good viscosity and additive properties enabling immersed brakes to work properly, without chattering.

TICMA FLUID XT XTREM possesses excellent oxidation resistance, enabling longer oil change intervals.

USES

Mechanical transmissions: Gearboxes and axles, differentials, final drives and immersed brakes.

Hydraulic controls and power-assisted steering for construction machinery.

Wet clutches for construction machinery.

Characteristics	Standards	Units	Values
Density at 15°C	NF T60-101	kg/m ³	881
Kinematic viscosity at 40°C	NF T60-100	mm ² /s	60
Kinematic viscosity at 100°C	NF T60-100	mm ² /s	9.80
Viscosity index	NF T60-136	-	145
Flash point	ISO 2592	°C	-42
TBN (alkaline reserve)	ASTM D2896	Mg KOH/g	9.9

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: VI-IGOL001-1510

Published: 09/10/2015