

A mineral absorbent.

## DESCRIPTION & APPLICATIONS

A chemically inert natural absorbent comprising clay particles sized mainly between 60 and 100 microns.

Completely safe absorption of liquids, in particular hydrocarbons, from workshops and access ways.

Contains at least 70% sepiolite.

Particle size:

Size (microns)	%
>600	8 max.
600-425	12 ±4
425-250	42 ±10
250-150	36 ±10
150-100	9 ±6
100-75	5 max.
<75	5 max.

## ADVANTAGES

- Absorbs any liquid
- Non-volatile (low dust, usable outdoors)
- Does not stain the floor
- Does not form a slippery sludge
- Simple to apply

Characteristics	Standards	Units	Values
Apparent density	BS 1460	kg/m <sup>3</sup>	690
pH	-	-	8 ±1
Hardness	Mohs scale	-	2 – 2.5
Water absorption power	Ford method	%	135 ml/100 g
Oil absorption power	Ford method	%	100 ml/100 g

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: X-175-1503  
Published: 01/04/2015