

A new-generation high-performance additive usable for treating fuel in any diesel engine vehicle.

ADVANTAGES

Regular use of ACTIVdiesel ensures the following:

- Reduced fuel consumption
- Injection components lubricated
- Clean intake systems
- Combustion chambers in perfect condition
- No deposits promoting valve or segment sticking
- Reduced engine noise level
- Reduced pollutant smoke emissions
- Lower filterability threshold temperature

ACTIVdiesel facilitates cold starting.

ACTIVdiesel prevents clogging of the engine and EGR valve.

USES

ACTIVdiesel is usable on any type of diesel engine: naturally aspirated, TDI, HDI, DCI, common rail.

ACTIVdiesel is suitable for any diesel vehicles, with or without turbo.

ACTIVdiesel is a preventive and curative product.

ACTIVdiesel is harmless to oxidation catalyts and particulate filters.

For the automotive sector, ACTIVdiesel comes in a single-dose 300 ml bottle, for use as a top-up treatment.

This operation should be repeated every 2000 km.

An overdose of ACTIVdiesel has no adverse effects on engine operation. A dose of ACTIVdiesel can treat a vehicle possessing a lower capacity tank.

Advice: two treatments with ACTIVdiesel are recommended for one oil change interval.

For other applications, use 1 L of ACTIVdiesel for 160 L of fuel.

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: X-94-1503
Published: 27/03/2015