

**A gel codex mineral oil, specially formulated for use in wet environments, with PTFE (polytetrafluoroethylene) additives.
Reserved for professional use.**

PERFORMANCES

All the components of this aerosol formulation have been approved by the American body NSF for incidental food contact: NSF H1 No. 145995 aerosol.

Physico-chemical characteristics of active ingredient:

- Appearance: buttery
- Range of use: -20 to +180°C (up to 200°C peak)
- No drop point
- 4-ball shell test: 300 kg
- Non-inflammable propellant gas

USES

GELFLON is recommended in agri-business in case of incidental contact (bakery, industrial, biscuit factory, dairy, cannery or slaughter house, etc.).
GELFLON can also be used in the plumbing, mechanical and automotive fields.
Its use is recommended wherever a non-soiling lubricant is required.
It can be removed by organic solvents.

INSTRUCTIONS FOR USE:

Clean the parts to be treated before application

- Shake the aerosol can vigorously.
- Spray onto the parts to be treated.
- Use the capillary tube for hard-to-access spots.

PACKAGING

- Box of 6 aerosol cans
- Nominal capacity: 650 ml -- Net volume: 400 ml
- Propellant gas: CO2

The aerosol cans must be used within one year of delivery for optimum use; returns will not be accepted after this time.

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: XVII-79-A-1603
Published: 14/03/2016