

## A lubricant for boat diesel engines.

Formulated from base oils refined with a high-quality solvent, plus multi-purpose additives.

### PERFORMANCES

#### Standards:

API CF

#### Specifications:

MII-L-2104C

### ADVANTAGES

#### Characteristics:

- very good oxidation stability
- stable viscosity index
- excellent detergent and dispersant power
- good capacity to neutralise acidic compounds appearing upon combustion of diesel fuel distillate
- outstanding anti-wear, anti-corrosion and anti-foaming properties
- low pour point
- good water separation power.

This boat oil can be used as a lubricating oil in both high-speed and medium-speed diesel boat engines, with or without turbocharger, when using fuel distillates with sulfur percentages of up to 1.8%. This oil can also be used for inboard gear transmissions.

Characteristics	Standards	Units	Values
Density at 15°C		kg/l	0.900
Viscosity at 40°C		mm <sup>2</sup> /s	138.00
Viscosity at 100°C		mm <sup>2</sup> /s	14.40
Viscosity index		-	103
COC flash point		°C	254
Pour point		°C	-22
Alkalinity		mg KOH/g	20.3
Sulfated ash		%	2.74

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: III-93-C-1503

Published: 20/03/2015