

A lubricant in the form of an anti-seize paste comprising aluminium microparticles.

PERFORMANCES

Range of use: -20 to + 600°C

ADVANTAGES

Anti-wear and anti-corrosion properties.

Protection

Permanent protection for mechanical parts with fitted, screwed or bolted joints, facilitating dismantling even after a long period out of use.

Application

By brush or cloth.

USES

Automobiles / Agriculture / Construction / Industry

Bolts, nuts, chains and cables for equipment working outdoors or exposed to aggressive atmospheres. Studs, threads, cylinder head gaskets, bolts and gaskets for tubing, valves, burners, furnace chains, and plastic injection subject to high temperatures.

Crane studs and rollers, metal scaffolding, bucket chains, naval or mining equipment, gaskets, packing.

Sheet metal working and forming, wire-drawing, joints, valve stems and bolts used in metallurgy.

Lubrication and protection of joints exposed to high furnace temperatures (up to 600 degrees).

Characteristics	Standards	Units	Values
Colour	-	-	Reddish
NLGI grade	-	-	1
Penetration	NFT 60-132	1/10 mm	310-340

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref. : IX-28-SP-1509
Date of publication : 06/10/2016