

Multipurpose grease, based on lithium soap and refined mineral base oils.

## PERFORMANCES

DIN 51502:KP2K-20  
ISO 6743 / 12924:L-XB(F)CHA2

Drop point: > 185°C  
Working range: -20 à + 140°C

## ADVANTAGES

Automobiles / HGVs / Agricultural machines / Public Works machines  
Multipurpose grease for all organs uncharged (wheel hubs), not requiring extreme pressure product.

### Industry

For the general non-extreme pressure lubrication.  
All bearings and bearings rotating at high speed (up to 3000 rev / min) under low load.

## USES

- Excellent adhesion
- Excellent lubricity
- An excellent operating performance in all working conditions.
- A perfect injectability.

Characteristics	Standards	Units	Values
Colour	-	-	Blonde
Texture	-	-	Smooth
NLGI Grade	-	-	2
Worked penetration 60	NF T 60-132	1/10 mm	265/295
Worked penetration 100000	NF T 60-132	1/10 mm	330
Water resistance	-	-	insoluble

*Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.*

Document ref. : IX-02-1510  
Date of publication : 19/07/2016