



## PROBEOL 2T TR

**A top-of-the-range synthetic oil for 2-stroke engines.**

Biodegradability >64% (standard OECD 301 B).

### PERFORMANCES

**Specifications:**

JASO FC (Anti-smoke)

ISO-L-EGD

### ADVANTAGES

Formulated from complex biodegradable esters and a high-performance additives system which enhances its lubricating power and its oxidation resistance.

A biodegradable lubricant, emitting very little smoke in the exhaust.

It yielded excellent results in tests on direct-injection 2-stroke engines.

### USES

PROBEOL 2T TR was developed for any type of the most demanding 2-stroke engine with separate or mixed greasing, including engines using new direct injection technology.

Product coloured blue to reveal its presence in the fuel.

In mixture, use 2 % to 4 % (according to manufacturer's recommendations).

Characteristics	Standards	Units	Values
Colour	Visual	-	Blue
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	44
Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.2
Viscosity index	NF T 60-136	-	161
Pour point	ASTM D97	°C	-42
COC flash point	ASTM D92	°C	224
Biodegradability	OECD 301 B	%	>64

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: II-115-N-1508

Published: 03/08/2015

