



PROBEOL SAT 46

A synthetic, biodegradable hydraulic fluid, formulated based on petrochemical-derived saturated esters, and more than 50% renewable, which contribute to protecting and preserving the environment.

PERFORMANCES

Specifications:

ISO 15380 (HEES)

DIN 51524-2

DIN 51524-3

ADVANTAGES

PROBEOL SAT possesses a high natural viscosity index, which reduces viscosity variations with temperature, and natural lubricity properties which contribute to reducing wear of lubricated components.

PROBEOL SAT features excellent oxidation resistance and good thermal stability.

USES

PROBEOL SAT must be used as a hydraulic fluid in applications where the environmental pollution risks are high: forests, near water courses, ecologically sensitive areas. PROBEOL SAT can be used in hydraulic systems working at moderate temperatures (<110°C).

Characteristics	Standards	Units	Values
Density at 15°C	NFT 60-106	kg/m ³	905
Flash point	NFT 60-118	°C	239
Pour point	ASTM D 97	°C	-39
Kinematic viscosity at 40°C	NFT 60-100	mm ² /s	47.3
Kinematic viscosity at 100°C	NFT 60-100	mm ² /s	8.1
Ultimate biodegradability	OECD 301 C, D, E, F	%	60
Viscosity index	NFT 60-136	-	144

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: VII-112-1508

Published: 04/08/2015

