

Semi-synthetic oil.

High-performance lubricant for Petrol injection and multi-valve, direct injection diesel engines, common rail, private cars requiring oils meeting ACEA A3/B4 specifications.

PERFORMANCES

Standards: ACEA A3/B4-08
API SL/CF

Specifications:
Mercedes Benz MB p.229.1

ORGANISATIONS and MANUFACTURERS - Scope of application -

ACEA A3/B4: for "High-Performance" Direct Injection Petrol and Diesel engines.

MB 229.1: for all Mercedes engines since 1997.ACEA A3/B3 + engine tests with standard oil change interval

API SL: Meets the requirements of modern engines from 2001 based on particular American Petroleum Institute specifications.

API CF: Diesel from 1994 (not recommended for LV in EU).

Characteristics	Standards	Units	Values
Density at 15°C	NF T 60-101	kg/m ³	876
Viscosity 40°C	ASTM D445	mm ² /s	101.8
Viscosity 100°C	ASTM D445	mm ² /s	14.6
Viscosity index	NF T 60-136	-	148
Pour point	ASTM D2602	°C	-30
Flash point	NF T 60-118	°C	238

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref.: I-31-1507
Date of publication: 29/07/2015

Technical data sheet