

A mineral oil-based lubricant for 2-stroke outboard engines with separate or mixed greasing.

## PERFORMANCES

**Standards:**

API TD

**Specifications:**

**NMMA TC-W3®\*** (Reference RL-50391)  
NMMA TC-W; TC-W II

\* **Approved quality.** Use recommended under manufacturers' warranties

## ADVANTAGES

PROSURF 2T HORS-BORD TC-W3 meets the highest level standards defined by NMMA, and has passed all the engine tests, relating in particular to:

- Extremely tough anti-wear and anti-deposit properties
- Excellent oil detergency
- Prevents spark plug clogging and fouling
- Prevents segment sticking at high temperatures
- Very high lubricating power
- Engine service life

Formulated from very high-quality mineral base oils and very high-performance ashless additives.

PROSURF 2T HORS-BORD TC-W3 is completely tailored to the hottest modern engines, new injection technologies, new fuels and new pollution control regulations.

## USES

Specially designed for high-performance 2-stroke outboard engines, running on lead-free petrol or petrol with potassium additives.

Separate greasing, or in a 1 or 2 % mixture in the fuel, depending on the manufacturer's recommendations.

The canister is equipped with a graduated dosing cap to facilitate dosing in the fuel. Product coloured to reveal its presence in the fuel.

Characteristics	Standards	Units	Values
Density at 15°C	NF T 60-101	kg/m <sup>3</sup>	875
Kinematic viscosity at 40°C	NF T 60-100	mm <sup>2</sup> /s	44.3
Kinematic viscosity at 100°C	NF T 60-100	mm <sup>2</sup> /s	7.1
Viscosity index	NF T 60-136	-	120
Pour point	NF T 60-105	°C	- 33
COC flash point	NF T 60-118	°C	110

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: II-83-1503  
Published: 20/03/2015

Technical data sheet