

A synthetic lubricant for direct injection 2-stroke water scooter and jet ski engines.

PERFORMANCES

Standards: API TC
ISO-L-EGD
JASO FC

ADVANTAGES

PROSURF 2T SI is formulated from esters, synthetic bases and additives.

The esters give PROSURF 2T SI remarkable lubricity properties, and an enhanced biodegradability rating compared to conventional oils.

The synthetic bases enable smoke-free combustion, and thereby improve the non-polluting properties of direct-injection 2-stroke engines.

The low-ash additives provide detergent and dispersion characteristics which help keep engines and various lubricated components clean.

Characteristics	Methods	Units	Values
Colour	visual	-	purple
Density at 15°C	NF T 60-101	kg/m ³	912
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	41.6
Kinematic viscosity at 100°C	NF T 60-100	mm ² /s	7.76
Viscosity index	NF T 60-136	-	159
COC flash point	NF T 60-118	°C	102

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: II-87-1503
Published: 20/03/2015