

A specific lubricant for YANMAR and VOLKSWAGEN inboard Diesel engines.

## PERFORMANCES

### Standards:

ACEA A3/B4/C3

API SM/CF

### Specifications:

BMW LL-04

VW 504.00/507.00

## ADVANTAGES

PROSURF 4T YW 5W-30 was exclusively developed for Yanmar and Volkswagen marine engines, but is also perfectly suitable for other 4-stroke inboard engines requiring ACEA A3/B4/C3 performance levels.

Its detergent power is able to keep the engine clean, free from lacquer or varnish deposits. The additives are also able to protect the engine against moisture damage: rust and corrosion.

PROSURF 4T YW 5W-30 contains synthetic bases and additives giving it a very high thermal stability and high oxidation resistance.

Characteristics	Standards	Units	Values
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	73.4
Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.9
Viscosity index	NF T 60-136		158
Pour point	ASTM D2602	mPa.s	-45
Flash point	ASTM D92	°C	209

*The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.*

Document ref.: I-85-L-1503 A02

Published: 20/03/2015