

A 100% synthetic biodegradable lubricant for 2-stroke outboard engines with separate or mixed greasing.

PERFORMANCES

Standards:
API TD

Specifications:
NMMA TC-W3®* (Reference RL 90042R)
NMMA TC-W; TC-W II

* **Approved quality.** Use recommended under manufacturers' warranties

ADVANTAGES

PROSURF AQUASYNTH 2T TC-W3 was formulated from a very high-quality biodegradable synthetic ester base, in combination with ashless additives.

This lubricant meets the highest level standards defined by **NMMA**, and has passed all the engine tests, relating in particular to:

- Extremely tough anti-wear and anti-deposit properties
- Excellent oil detergency
- Prevents spark plug clogging and fouling
- Prevents segment sticking at high temperatures
- Very high lubricating power
- Engine service life

USES

An extremely top-of-the-range 2-stroke oil, specially designed for high-performance 2-stroke outboard engines, running on lead-free petrol or petrol with potassium additives.
Separate greasing, or in mixture (use 1% or 2%, according to manufacturer's recommendations).

Usable under the toughest conditions (racing, very cold weather, etc.)

The canister is equipped with a graduated dosing cap to facilitate dosing in the fuel.

Product coloured to reveal its presence in the fuel.

Characteristics	Methods	Units	Values
Density at 15°C	NF T 60-101	kg/m ³	913
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	36
Kinematic viscosity at 100°C	NF T 60-100	mm ² /s	7
Viscosity index	NF T 60-136	-	177
Pour point	NF T 60-105	°C	-32
COC flash point	NF T 60-118	°C	113
Biodegradability	OECD 301 B	%	≥ 62

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: II-116-1508
 Published: 04/08/2015

Technical data sheet