

Solvent-based protective fluid.

DESCRIPTION & APPLICATIONS

Sonifat 2040 DW is a rust inhibitor that removes moisture.

Sonifat 2040 DW adheres very well to metal due to its strong polarity, providing long-lasting protection of any coated surfaces.

Sonifat 2040 DW eliminates any traces of grease and impurities by leaving a protective film deposit.

Sonifat 2040 DW acts deep down to combat corrosion in the sublayers and prevents any pits from forming and developing.

Sonifat 2040 DW possesses water-repellent properties. It removes water from contacts and is suitable for all applications (excluding electrical systems), wherever the need for drying and protecting is necessary.

USES

All mechanical industries.

Application by:

- nebulisation (aerosol or spray gun)
- painting using a brush
- immersion

Characteristics	Standards	Units	Values
Appearance / Color	-	-	Fluid/Brown
Density at 15°C	NFT 60-101	kg/m ³	795
Flash point VO	NFT 60-118	°C	47

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref. : X-146-1601
Date of publication : 25/04/2016

Technical data sheet