

**Adhesive mixture of bitumen and lithium soaps containing molybdenum bisulfide (MoS₂).
Professional use only.**

DESCRIPTION

A range of additives give it extreme pressure properties.
It is dispersed using a solvent to ensure correct film formation and application.
The solvent used is inflammable, but does not contain chlorine.

USES

Ideal for: chains, cable, cogs, crowns and exposed gears.
Adhesive lubricant and protection against atmospheric compounds.
A range of industries: cement factories, quarries, construction, marine technology and civil engineering.

INSTRUCTIONS FOR USE

Before use, shake well, until the pea loosens and freely moves inside the can.
Hold the can 20cm away from the surface and spray in a right to left movement to ensure good cover and penetration.

Hold the can upside down and bleed it after use to ensure the spray nozzle remains operational.

Nozzle blockages are caused by inadequate bleeding.

For an optimal use, sprays must be used in the year following the delivery, returns will not be accepted after this deadline.

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Document ref. : XVII-55-1511
Date of publication : 03/11/2015