

**CLEANOX P is an emulsifiable solvent preparation intended for cold cleaning engines and all metal parts soiled with greasy deposits.**

Thanks to its wetting power, CLEANOX P penetrates these deposits, enabling them to be detached and removed by simply washing with water.

**USES**

**Professional use.**

Cold degreasing of engines, machines and metal parts.

Spray sparingly onto the parts to be treated with a spray gun. Allow 15 to 20 minutes for the product to penetrate the grease, sludge, tar, etc. covering the parts.

Rinse with a water jet. All the residue will be carried away.

For small parts, allow them to soak for approximately 10 minutes in a bath of CLEANOX P. Then drain them and wash generously with water.

**Warning**

CLEANOX P is not suitable for degreasing machines using alkaline washing products.

Do not use close to a flame.

For prolonged handling, gloves are recommended. When spraying avoid breathing in the vapours.

Characteristics	Units	Standards	Values
Density at 15°C	kg/m <sup>3</sup>	NF T 60-172	846
Closed cup flash point	°C	NF M 07-019	80
Open cup flash point	°C	NF T 60-118	90
Fire point	°C	ASTM E 659	93
Kinematic viscosity at 20°C	mm <sup>2</sup> /s	ASTM D 445	2,8
Kauri-butanol index	ml	ASTM D 1133	30

*Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.*

Document ref. : X-73-1510  
Date of publication : 20/10/2015