

A mineral oil.

A lubricant specially designed for use in **Detroit 2-stroke diesel** engines requiring an **ash content of less than 1%**.

This lubricant possesses very good dispersive, anti-oxidant and anti-wear properties.

Suitable for application in any diesel engine: HGVs, construction machinery, agricultural machinery, buses, etc.

PERFORMANCES

Standards:

API CD II
API CF/CF-2

Specifications:

Detroit Diesel: 6V92TA-TEST
Caterpillar
Allison C3
Mack EO-J

Characteristics	Methods	Units	30	40	15W-40
Density at 15°C	NF T 60-101	kg/m ³	893	905	886
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	87.5	140.3	97.5
Viscosity index	NF T 60-136	-	110	108	160
Sulfated ash content	NF T 60143	% mass	0.95	0.96	0.96

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: III-IGOL010-1702
Published: 27/02/2017

Technical data sheet